

In the Claims:

Please cancel claims 5, 16-25, 30 and 67-68, and amend claims 1, 4, 7-8, 11, 26, 29, 31, 54 and 65, as follows:

1. (Currently amended) A preformed unibody diverter for directing water away from a building foundation comprising:

a generally vertical section having a first predetermined width;

first and second portions of said generally vertical section disposed at an angle with respect to one another;

an angled section extending downwardly from said generally vertical section at an obtuse angle therewith and having a second predetermined width, wherein said angled section includes first and second portions disposed at an obtuse angle with respect to one another; and

wherein said ~~first~~second predetermined width is substantially larger than said ~~second~~first predetermined width.

2. (Original) The diverter of claim 1 wherein said first and second portions are disposed at a generally right angle with respect to one another.

3. (Original) The diverter of claim 1 wherein said vertical section has a width of approximately ten inches.

4. (Currently amended) The diverter of claim ~~1~~3 wherein said angled section has a width of approximately 30 inches.

5. (Canceled)

6. (Original) The diverter of claim 1 wherein said first and second portions of said vertical section have a predetermined length of approximately 24 inches.

7. (Currently amended) The diverter of claim ~~1~~4 wherein said angled portion extends downwardly from said vertical portion at a grade of approximately 20%.

8. (Currently amended) The diverter of claim ~~1~~7 wherein said vertical section has a predetermined thickness.

9. (Original) The diverter of claim 8 wherein said vertical section has a predetermined thickness of approximately 0.045 inches (1 millimeter).

10. (Original) The diverter of claim 1 wherein said angled portion comprises rubber.

11. (Currently amended) The diverter of claim 1 wherein said vertical section comprises ~~PVC~~ polyvinylchloride.

12. (Original) The diverter of claim 1 wherein said vertical section includes an attachment system.

13. (Original) The diverter of claim 12 wherein said attachment system includes at least one fastener.

14. (Original) The diverter of claim 13 wherein said fastener comprises at least one bolt.

15. (Original) The diverter of claim 13 wherein said fastener comprises at least one threaded fastener.

16-25. (Canceled)

26. (Currently amended) A preformed diverter system for directing water away from a building foundation that includes one or more of an outside corner, inside corner and a generally planar surface, said system comprising:

a first unibody diverter body generally shaped to fit closely to the outside corner of the building foundation;

a second unibody diverter body generally shaped to fit closely to the generally planar surface of the building foundation; and

a third unibody diverter body generally shaped to fit closely to the inside corner of the building foundation ~~when the inside corner is present~~.

27. (Original) The diverter system of claim 26 wherein said first unibody diverter body includes a generally L-shaped vertical portion shaped to abut the outside corner of the building foundation and an angled portion that extends downwardly and away from both the vertical portion and the building foundation.

28. (Original) The diverter system of claim 27 wherein said vertical portion of said first unibody diverter body has a width of approximately ten inches.

29. (Currently amended) The diverter system of claim 27 wherein said angled ~~section~~ portion of said first unibody diverter body has a width of approximately 30 inches.

30. (Canceled)

31. (Currently amended) The diverter system of claim ~~27~~29 wherein said angled portion of said first unibody diverter body extends downwardly from said vertical portion at a grade of approximately 20%.

32. (Original) The diverter system of claim 27 wherein said vertical portion of said first unibody diverter body includes a first half and a second half each having a predetermined length of approximately 24 inches.

33. (Original) The diverter system of claim 27 wherein said vertical section of said first unibody diverter body includes an attachment system.

34. (Original) The diverter system of claim 27 wherein said attachment system includes at least one fastener.

35. (Original) The diverter system of claim 27 wherein said second unibody diverter body includes a vertical portion shaped to abut the generally planar surface of the building foundation and an angled portion that extends downwardly and away from both the vertical portion and the building foundation.

36. (Original) The diverter system of claim 35 wherein said vertical portion of said second unibody diverter body has a predetermined width of approximately 10 inches.

37. (Original) The diverter system of claim 35 wherein said vertical portion of said second unibody diverter body has a predetermined width corresponding to a distance between two inside corners of the building foundation.

38. (Original) The diverter system of claim 35 wherein said vertical portion of said second unibody diverter body has a predetermined width corresponding to a distance between two outside corners of the building foundation.

39. (Original) The diverter system of claim 35 wherein said vertical portion of said second unibody diverter body has a predetermined width corresponding to a distance between an inside corner and an outside corner of the building foundation.

40. (Original) The diverter system of claim 35 wherein said angled portion of said second unibody diverter body has a predetermined width of approximately 30 inches.

41. (Original) The diverter system of claim 35 wherein a ratio of the widths of said vertical section and said angled section of said second unibody diverter body is between approximately 1:1 and 1:10.

42. (Original) The diverter system of claim 35 wherein said angled portion of said second unibody diverter body extends downwardly from said vertical portion at a grade of approximately 20%.

43. (Original) The diverter system of claim 35 wherein said vertical portion of said second unibody diverter body is generally planar and has a predetermined length of approximately 27 inches.

44. (Original) The diverter system of claim 35 wherein said vertical portion of said second unibody diverter body includes an attachment system.

45. (Original) The diverter system of claim 35 wherein said attachment system includes at least one fastener.

46. (Original) The diverter system of claim 26 wherein said third unibody diverter body includes a vertical portion generally shaped to fit closely to the inside corner of the building foundation when the inside corner is present and an angled portion that extends downwardly and away from both the vertical portion and the building foundation.

47. (Original) The diverter system of claim 46 wherein said vertical portion of said third unibody diverter body has a width of approximately ten inches.

48. (Original) The diverter system of claim 46 wherein said angled section of said third unibody diverter body has a width of approximately 30 inches.

49. (Original) The diverter system of claim 46 wherein a ratio of the widths of said vertical section and said angled section of said third unibody diverter body is between approximately 1:1 and 1:10.

50. (Original) The diverter system of claim 46 wherein said angled portion of said third unibody diverter body extends downwardly from said vertical portion at a grade of approximately 20%.

51. (Original) The diverter system of claim 46 wherein said vertical portion of said third unibody diverter body includes a first half and a second half each having a predetermined length of approximately 44 inches.

52. (Original) The diverter system of claim 46 wherein said vertical section of said third unibody diverter body includes an attachment system.

53. (Original) The diverter system of claim 46 wherein said attachment system includes at least one fastener.



54. (Currently amended) A preformed unibody diverter for directing water away from a building foundation comprising:

a generally vertical section having a first predetermined width;

an angled section having a second predetermined width and being angled downwardly and away from both said vertical section and the building foundation; and

wherein said ~~first~~second predetermined width is substantially larger than said ~~second~~first predetermined width.

55-64. (Withdrawn)

65. (Currently amended) A preformed unibody diverter for directing water away from a building foundation comprising:

a diverter body generally shaped to surround and fit closely to a generally cylindrical post of the building foundation, wherein said diverter body includes a vertical portion and an angled portion that extends downwardly and away from both said vertical portion and said cylindrical post of said building foundation.

66. (Original) The diverter of claim 65 further comprising a through-cut disposed on said vertical portion and said angled portion.

67-68. (Canceled)